

A white cylindrical water heater with a black top and bottom. A brass drain valve is visible on the lower right side. The brand name 'WEIL-McLAIN' and 'AQUA' are printed on a small label near the top.

Built to take the
harshest water
conditions

The non-metallic Aqua Pro™ is the right choice to stand up to corrosion.


The Aqua Pro composite tank construction is ideal for all types of water conditions – especially the harshest environments. Check out these additional design features:

- Lightweight, easily maneuvered non-metallic tank
- Available in 4 sizes: 30, 50, 80, and 119 gallons
- No anode to check, no annual maintenance
- Convenient top connections
- Seamless tank construction, no welds
- Digital temperature control
- Removable copper finned high-output coil
- Durable brass drain valve
- Low heat loss, 2" foam insulation



Leverage the power and efficiency of your boiler for domestic hot water with the Aqua Pro indirect-fired water heater. Flexible to fit a broad range of applications, it's designed to install easily into any system.



Aqua Pro Specs				
	30 Gallon	55 Gallon	80 Gallon	119 Gallon
Ratings				
1st Hour Rating (GPH)	199	217	381	477
Continuous Draw Rating (GPH)	177	177	315	381
Standby Heat Loss (F/HR)	.8	.6	.4	.4
Minimum Heat Output Rate (MBH)	115	115	199	244
Dimensions				
Height to Fitting (in)	40 ½"	41"	53 ½"	74"
Overall Diameter (in)	22 ¾"	28"	28"	28"
Inner Tank Diameter (in)	18"	24"	24"	24"
Approx. Shipping Weight (lbs)	70	95	125	155
Pipe Sizes (MNPT) - All Top Connections	¾"	¾"	DHW 1 ½" Boiler 1"	DHW 1 ½" Boiler 1"



SIMPLIFIED SOLUTIONS FOR OUR COMPLEX WORLD™